



MapleSolutions

3019 Lake Road, Dollard Des Ormeaux, QC, H9B 2R3 Canada - Tel : 1 (514) 472 0094 www.maplechemicals.com

TECHNICAL BULLETIN

STATEMENT OF USE

MA-PRINT TJ is a specially designed pigment pad dyeing auxiliary and dispersing agent that effectively disperses pigments and prevents build-up of acrylic binder systems. Smoother dyeings are also attainable by the use of **MA-PRINT TJ**.

TYPICAL PROPERTIES

Chemical Composition	Proprietary
Appearance	Clear, liquid
Ionic Nature	Nonionic
pH (10%)	Approx. 5.0
Solubility	Readily dispersible in water
Density, lb/gal	Approx. 8.4

ADVANTAGES

- Excellent dispersing properties for pigments.
- Stable to resin/catalyst systems
- Prevents build-up on rolls and pad boxes of acrylic binder systems.
- Produces smoother dyeings (helps mask "reedy" appearance on polyester/cotton blends)

APPLICATION

MA-PRINT TJ is added directly to the pigment pad dyeing mix. Typical usage levels are 5-10g/L (0.5-1.0% on-the-weight-of-the bath).

PACKAGING

Available in returnable drums.

PHYSIOLOGICAL DATA

For Industrial Use Only: The usual precautions in keeping chemicals from the eyes and skin and avoiding ingestion and prolonged inhalation of vapors should be observed.

While every care has been taken to ensure the accuracy of the information contained in this publication, no warranty or liability will be accepted as the conditions of usage are beyond our control. Product specifications can be provided upon request.

Our Technical Sales Department is available to assist customers in preparing formulae and procedures to suit their specific requirements. Production trials are recommended to determine effectiveness. Process information submitted by our customers will be treated in confidence.